

# Paper Cutter Store

Phone: 1-866-432-0042 / INT'L 1-718-859-0917 Fax: 718-228-7476 We Will Match Any Current Web Advertised Price!

## RotaTrim T1250 - Technical Series Cutter 50 Inch Heavy-Duty Manual Rotary Trimmer

[http://www.papercutterstore.com/49\\_Inch\\_Heavy\\_Duty\\_Manual\\_Rotary\\_Trimmer\\_1345\\_13078.html](http://www.papercutterstore.com/49_Inch_Heavy_Duty_Manual_Rotary_Trimmer_1345_13078.html)



PRODUCT ID # : 13078

### PRODUCT SPECIFICATION

Max. Cut Thickness	.19 in.
Max. Paper Cutting Length	49 in.

### DIMENSIONS

Weight:	37.00 lbs.
Width:	17.00 inches
Length:	66.00 inches
Height:	8.00 inches

### OUR PRICE

LIST PRICE :	\$1250.00
INSTANT SAVING :	- \$91.00
SALES PRICE :	<b>\$1159.00</b>
SHIPPING CHARGE :	<b>FREE</b>

### PRODUCT DESCRIPTION

The RotaTrim T1250 Technical Manual Rotary Trimmer cuts paper up to 50 long and stacks of paper up to 35 sheets thick 3 16 inch . Its fully enclosed, self sharpening tungsten steel cutting wheel is driven by two spring loaded pressure rollers for a secure clamping action. The overload plate is designed to prevent damage from accidental overload and can be easily removed for bi directional cutting of thinner materials. Its aluminum clamping strip automatically releases material when the cutting head reaches the end of the track. The RotaTrim T1250 slices effortlessly through almost any flexible sheet material up to 4mm thick. It is equally at home with thin films and foils due to the unique self adjusting triple roller Cutting Head.

### PRODUCT FEATURES

A 10-1/2 inch rule and squaring arm is factory installed onto an all-metal base. Chromed 1-1/2 inch square steel guide rail and all metal construction eliminates distortion. Extruded satin finish aluminum baseboard with parallel indents is strong and warp-free. RotaTrim Technical Cutters are manufactured under ISO 9002 standards. Self-sharpening Sheffield tungsten steel cutting wheel and counterblade. Transparent clamp strip and rubber gripper for firm positive clamping action. Two way cutting optoin by removing cover plate.